

ORVV ORVV-SB

(心タイプ)

心数	導体(錫メッキ軟銅線)			絶縁体(ETFE)		外被(耐油耐熱PVC)			電気特性		
	サイズ	構成	外径 (標準)	厚さ (標準)	外径 (標準)	厚さ (標準)	標準外径 (シールド なし)	標準外径 (シールド つき)	導体抵抗	絶縁抵抗	耐電圧
	SQ(mm <sup>2</sup> )	mm	mm	mm	mm	mm	mm	mm	Ω/km(20°C)	MΩ・km(20°C)	V/分
2C	0.2	7/0.18	0.54	0.3	1.14	1.0	4.4	5.0	~115	50~	500
3C							4.6	5.2			
4C							4.9	5.5			
5C							5.2	5.8			
6C							5.5	6.1			
7C							5.9	6.5			
8C							6.3	6.9			
10C							6.4	7.0			
12C							6.7	7.3			
15C							7.2	7.8			
16C							7.5	8.1			
20C							8.0	8.6			
25C							8.7	9.3			
2C	0.3	12/0.18	0.72	0.4	1.52	1.0	5.1	5.7	~67	50~	500
3C							5.4	6.0			
4C							5.8	6.4			
5C							6.2	6.8			
6C							6.7	7.3			
7C							7.1	7.7			
8C							7.7	8.3			
10C							7.8	8.4			
12C							8.2	8.8			
15C							8.9	9.5			
16C							9.3	10.0			
20C							9.9	10.6			
25C							10.9	11.6			
2C	0.5	20/0.18	0.93	0.41	1.75	1.0	5.6	6.2	~40	50~	500
3C							5.8	6.4			
4C							6.3	6.9			
5C							6.8	7.4			
6C							7.3	7.9			
7C							7.8	8.4			
8C							8.4	9.0			
10C							8.6	9.2			
12C							9.0	9.6			
15C							9.8	10.5			
16C							10.3	11.0			
20C							11.0	11.7			
25C							12.1	12.9			
2C	0.75	30/0.18	1.14	0.8	2.74	1.0	7.6	8.2	~27	50~	1500
3C							8.0	8.6			
4C							8.7	9.3			
5C							9.5	10.3			
6C							10.3	11.0			
7C							11.2	11.9			
8C							12.1	12.9			
10C							12.5	13.3			
12C							13.3	14.1			
15C							14.6	15.4			
16C							15.3	16.1			
20C							16.6	17.5			
25C							18.3	19.3			
2C	1.25	50/0.18	1.47	0.8	3.07	1.0	8.2	8.8	~16	50~	1500
3C							8.7	9.3			
4C							9.5	10.2			
5C							10.4	11.1			
6C							11.3	12.0			
7C							12.2	13.0			
8C							13.3	14.1			
10C							13.7	14.5			
12C							14.6	15.4			
15C							16.1	16.9			
16C							16.8	17.7			
20C							18.3	19.3			
25C							20.2	21.4			
2C	2	37/0.26	1.83	0.8	3.43	1.0	9.0	9.6	~10.2	50~	1500
3C							9.5	10.2			
4C							10.4	11.1			
5C							11.4	12.1			
6C							12.4	13.2			
7C							13.4	14.2			
8C							14.7	15.5			
10C							15.1	15.9			
12C							16.1	16.9			
15C							17.8	18.7			